

Breakout Fiber Patch Cords



Products Details

Applications

- It is widely used in optical network scenarios such as LAN, ODF and data center etc.

Specifications

Connector Type	SC、LC、FC、ST	Connector	PC、UPC、APC
fiber type	OS2/OM1/OM2/OM3/OM4/OM5	Subunit Cable OD	0.9mm、2.0mm、
Insertion Loss (dB)	SM≤0.7dB、MM≤0.5dB	Return Loss (dB)	SM-PC≥30dB、SM-UPC≥50dB、MM≥25dB
Fiber core	4F、6F、8F、12F	Jacket	LSZH/PVC
Operating Environment		- 25°C ~ +70°C	

Product purchasing information

①A-Connector	②A-Polish Method	③B-Connector	④B-Polish Method	⑤FiberType	⑥Fiber Core	⑦Jacket	⑧Cable OD	⑨Length
a≈SC	a≈UPC	a≈SC	a≈UPC	a≈G652D	a≈4F	a≈PVC	a≈0.9mm	a≈3m
b≈LC	b≈APC	b≈LC	b≈APC	b≈OM1/OM2	b≈6F	b≈LSZH	b≈2.0mm	b≈5m
c≈FC	c≈PC	c≈FC	c≈PC	c≈OM3	c≈8F	---	---	c≈10m
d≈ST	---	d≈ST	---	d≈OM4	d≈12F	---	---	d≈20m
---	---	---	---	e≈OM5	Customized	---	---	Customized

①～⑨Need customers choice