

10G万兆光模块



产品详情

产品应用

- 适用于万兆以太网，城域网，接入网，无线， SDH/SONET通信设备，等等

主要参数

封装	连接器	速率	工作波长	传输距离	激光器类型	发射光功率	探测器类型	接收光功率
SFP+	LC	10G	850nm	300m	VCSEL	-6~-1dBm	PIN	-10~0.5dBm
SFP+	LC	10G	1310nm	2km	FP	-6~-0.5dBm	PIN	-14.4~0.5dBm
SFP+	LC	10G	1310nm	10km	DFB	-6~-0.5dBm	PIN	-14.4~0.5dBm
SFP+	LC	10G	1310nm	20km	DFB	-3~3dBm	PIN	-14.4~0.5dBm
SFP+	LC	10G	1550nm	40km	EML	-1~3dBm	PIN	-15.8~0.5dBm
SFP+	LC	10G	1550nm	80km	EML	0~4dBm	APD	-23~-6dBm
SFP+	LC	10G	1270nm/1330nm	10km	DFB	-6~-0.5dBm	PIN	-15~0.5dBm
SFP+	LC	10G	1330nm/1270nm	10km	DFB	-6~-0.5dBm	PIN	-15~0.5dBm
SFP+	LC	10G	1270nm/1330nm	20km	DFB	-3~3dBm	PIN	-15~0.5dBm
SFP+	LC	10G	1330nm/1270nm	20km	DFB	-3~3dBm	PIN	-15~0.5dBm
SFP+	LC	10G	1270nm/1330nm	40km	DFB	0~5dBm	PIN	-15~0.5dBm
SFP+	LC	10G	1330nm/1270nm	40km	DFB	0~5dBm	PIN	-15~0.5dBm
SFP+	LC	10G	1270nm/1330nm	60km	DFB	0~5dBm	APD	-20~-6dBm
SFP+	LC	10G	1330nm/1270nm	60km	DFB	0~5dBm	APD	-20~-6dBm
SFP+	LC	10G	1490nm/1550nm	80km	EML	0~4dBm	APD	-24~-7dBm